









SEE NO EVIL

**VAN DAMME ENHANCED PERFORMANCE UHD VISION 12GHZ CABLE
RG11/U**



The Van Damme Enhanced Performance HD 12G Vision coaxial is based around the industry standard RG11/U. Its precision construction ensures that electrical performance is optimised, ensuring trouble free performance with 4K Single-link 12 Gb/s UHD TV, SMPTE 424M and 292M HD-SDI signals as well as SDI and analogue video.

APPLICATIONS	MATERIALS	KEY BENEFITS
 Broadcast  Video  Presentations	 Oxygen free copper  Skin Foam Skin Polyethylene  Flexible PVC	 Precision 75 Ohm Impedance  Extended Transmission Length

SEE NO EVIL

Applications

- Extended transmission of UHD, HD-SDI, SDI and analogue video signals
- SMPTE 2082-1 12 Gb/s UHD TV
- SMPTE 2081-1 6 Gb/s UHD TV
- Designed for installation, touring, outside broadcast and other dynamic uses

Application Notes

- Use of precision 75 Ohm components throughout any signal chain is imperative
- See downloads for Transmission length guidelines

Mechanical Specification

Conductor	Silver plated oxygen free copper
Stranding	1 x 1.63 mm
Size	2.06 mm ² , AWG 14
Dielectric	Gas injected foam skin polyethylene
Diameter (mm)	7.10
Screen 1	Aluminium/polyester foil (bonded to insulation) > 100% coverage
Screen 2	Tinned oxygen free copper braid > 95% coverage
Screen 3	Aluminium/polyester foil (bonded to jacket)
Overall jacket	Flexible PVC composite Jet Black RAL 9005
Overall diameter (mm)	10.16 ± 0.25
Bend radius	15 x overall diameter
Operating temperature	-30 to +75 °C

Electrical Specification

Conductor resistance (Ohm/km)	< 8.2
Capacitance (pF/m)	51
Impedance (Ohms)	75 ± 5
Attenuation (dB/100m)	
100 MHz	4.10
135 MHz	4.63
180 MHz	5.30
270 MHz	6.43
720 MHz	10.73
1500 MHz	15.85
3000 MHz	23.20

Part Numbers and Description

Part Number	Description	Max. Reel Length
268-875-011	Van Damme Enhanced UHD Vision 12Ghz solid conductor coax RG11/U	500 m

Recommended BNC Connectors

339-112-011	Van Damme UHD 12G cable male RG11/U
-------------	-------------------------------------



SEE NO EVIL

Connector selection criteria:

Conductor	Dielectric diameter	Overall diameter	Summary
1 x 1.63 mm	7.11 mm	10.16 mm	(1.6/7.1/10.2)

Standards and Compliance

RoHS 3 (EU 2015/863) Restriction of Hazardous Substances

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals